

G = PF

Rohrgewinde DIN ISO 228-1

British Standard pipe thread DIN ISO 228-1/ Filetage tube DIN ISO 228-1

Filettatura Whitworth a Gas cilindrica, DIN ISO 228-1 /

Rosca para tubos DIN ISO 228-1, Norma Británica

Kurzeichen Thread size Désignation Diametro del filetto Dimensión rosca	Vorbohr-Ø Tapping drill size Ø de l'avant trou Diam. del preforo Dimensión broca (mm)	Muttergewinde Kern-Ø Minor diameter / Ø-intérieur Diametro del nocciolo Diám. Núcleo (mm)	
		min	max / mass
G 1/8-28	8,8	8,566	8,848
G 1/4-19	11,8	11,445	11,890
G 3/8-19	15,25	14,950	15,395
G 1/2-14	19	18,631	19,172
G 5/8-14	21	20,587	21,128
G 3/4-14	24,5	24,117	24,658
G 7/8-14	28,25	27,877	28,418
G 1-11	30,75	30,291	30,931
G 1 1/8-11	35,5	34,939	35,579
G 1 1/4-11	39,5	38,952	39,592
G 1 3/8-11	41,9	41,366	42,006
G 1 1/2-11	45,25	44,845	45,485
G 1 3/4-11	51	50,788	51,428
G 2-11	57	56,656	57,296
G 2 1/4-11	63,1	62,752	63,392
G 2 1/2-11	72,6	72,226	72,866
G 3-11	85,5	84,926	85,566