

Gewindekernlöcher für Gewindebohre
 Tapping drill sizes for taps / Avant-trous de
 taraudage / Prefori per maschi / Dimensiones de la
 broca previa para machos

Rp = PS

Whitworth Rohrgewinde ISO 7/1 und DIN 2999

Whitworth Standard parallel internal pipe thread ISO 7/1 and DIN 2999

Filetage Whitworth pour tubes DIN 2999

Filettatura Whitworth ISO 7/1 e DIN 2999

Rosca cilíndrica interna para tubos ISO 7/1 y DIN 2999, norma Whitworth

Kurzzeichen Thread size Désignation Diametro del filetto Dimensión rosca	Vorbohr-Ø Tapping drill size Ø de l'avant trou Diam. del preforo Dimensión broca (mm)	Muttergewinde Kern-Ø Minor diameter Ø-intérieur Diametro del nocciolo Diám. Núcleo max / mass (mm)
Rp 1/16	6,55	6,632
Rp 1/8	8,6	8,637
Rp 1/4	11,5	11,549
Rp 3/8	15	15,054
Rp 1/2	18,5	18,773
Rp 3/4	24	24,259
Rp 1	30,25	30,471
Rp 1 1/4	39	39,132
Rp 1 1/2	44,85	45,025
Rp 2	56,5	56,836
Rp 2 1/2	72,25	72,443
Rp 3	85	85,143